

Microphones Series

CM10, EC200, CB100 Paging Microphone; MP9810RII, PC1010R

Remote Paging Microphones



CM 10



EC 200



CB 100

FEATURES:

MP9810RII REMOTE PAGING MICROPHONE

- Up to 10 sets of MP9810P at remote place 1 km far away can be controlled.
- 1 MIC and 1 LINE input.
- Chime function.
- Muting function.

SPECIFICATIONS:

REMOTE PAGING MICROPHONE MP9810RII

Inputs	Mic: $5(\pm 1\text{mV})$, unbalanced Line: $1(\pm 0.1\text{V})$, unbalanced
Audio output	$1(\pm 0.1\text{V})$
Frequency response	Mic: 150Hz-15kHz($\pm 3\text{dB}$) ; Line: 20Hz-20kHz ($\pm 3\text{dB}$)
Signal to noise ratio	Mic input: greater than 60dB Line input: greater than 70dB
Protection	AC fuse 200mA
Power Requirement	AC 220-240V/50-60Hz
Outer Packing Size (mm)	(L×W×H) 430×260×135

Unit Size (mm)	(L×W×H) 270×180×55
Gross weight	2.1kg
Net weight	1.5kg

Specifications are subject to change without notice.

FEATURES :

REMOTE PAGING MICROPHONE PC1010R

- Maximum 100 zone selector
- 2 types of built-in 4 tone pre-announcement chimes with mute function
- RS-232 interface provides linking with PC-1010P Paging Selector with up to 1km remote control distance
- LINE IN port provides connection with audio source or PC-1011P Pre-amplifier for zone BGM or sound amplification
- Output level and line busy indication
- Power source:22VAC
- PC-1010R Remote Paging Microphone works with PC-1010P Paging Selector to achieve remote paging to each zone.
- Linking with 10 PC-1010P, maximum 100 zones can be controlled through the zone and range pushbutton combination operation on the panel.

SPECIFICATIONS:

REMOTE PAGING MICROPHONE PC1010R

Input	MIC:8.0mV, unbalanced; LINE: 1V, unbalanced
Output	1V
Frequency Response	MIC: 100Hz-15kHz; LINE: 20Hz-20kHz
S/N Ratio	MIC: input not less than 60dB; LINE input not less than 70dB
Protection	AC Fuse 200mA
Power Requirements	AC220V-240V/50-60Hz
Dimensions(W*H*D)	270*180*55(MM)
Net Weight	1.2kg
Gross Weight	1.5kg

Specifications are subject to change without notice.

FEATURES:

Paging Microphone

- Easy to use in different sites
- Plug & play function

- Turn on & off chime function
- Adjustable chime volume

SPECIFICATIONS:

MODEL	CM10	CB100	EC200	EC500
FREQ.RESP	100-16000Hz	250-6000Hz	50 - 15000Hz	80-12000Hz
IMPEDANCE	600Ω	500Ω	600Ω	600Ω
SENSITIVITY(at 1kHz)	-50dB±1dB	-74 dB	-54dB±3dB	-73 dB
DIMENSIONS(HxWx L)	250x190x130mm	100x60x50mm	420x150x150mm	367x122x162mm
WEIGHT	1.4kg	0.165kg	1.4kg	0.85kg

Specifications are subject to change without notice.

Note: See MP98 series and PC10 series for more details of MP9810RII and PC1010R Remote Paging Microphones.