

DH-IPC-HFW2100

1.3Mp CMOS HD Network Water-proof IR Mini Network Camera



DH-IPC-HFW2100P: 1.3 Megapixel CMOS, 25fps@720P, 15fps@1.3M, Lens: 6mm (3.6mm/8mm optional), IR LED, IP66, PoE

DH-IPC-HFW2100N: 1.3 Megapixel CMOS, 30fps@720P, 15fps@1.3M, Lens: 6mm (3.6mm/8mm optional), IR LED, IP66, PoE

Features

- > 1/3" 1.3 Megapixel Aptina CMOS image sensor
- > High-performance TI DaVinci series DSP
- > H.264&MJPEG video compression and JPEG image capture
- > Max 25/30fps@720P(1280×720) , 15fps@1.3M(1280×960) resolution
- > Dual encoding streams supported
- > Lens: 6mm (3.6mm/8mm optional)
- > Max. IR Distance: 20m
- > True Day/Night ICR
- > IP66 all-environments protection, 4000V thunder-proof, constant temperature automatic control & anti-fog
- > Support DC12V power supply, PoE
- > Built-in Web server, NVR, CMS(PSS/DSS) & DMSS

DH-IPC-HFW2100

Specifications

Model	DH-IPC-HFW2100P	DH-IPC-HFW2100N
General		
Processor	TI DaVinci Series DSP	
Operating System	Embedded LINUX	
Resource	Simultaneous remote monitoring, local recording and remote control	
User Interface	WEB, CMS(DSS/ PSS), DMSS, NVR	
Camera		
Image Sensor	1/3" 1.3 Megapixel Aptina CMOS	
Effective Pixels	1280 (H)×960(V)	
Electronic Shutter	Auto/Manual, 1/3~1/10000s	Auto/Manual, 1/4~1/10000s
Mini. Illumination	0.1LUX/F1.2(Color), 0.05LUX/F1.2(B/W) 0LUX(IR On)	
Signal Noise Ratio	> 50dB	
Gain Control	Auto/Manual	
White Balance	Auto/Manual	
Day/Night	ICR	
Lens Mount	M12	
Lens	Default: 6mm (3.6mm/8mm optional)	
Video		
Video Compression	H.264/MJPEG	
Image Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576/704×480)	
Encoding Speed	1.3M (1~15fps)+ D1(1~15fps)	1.3M (1~15fps)+ D1(1~15fps)
	720P(1~25fps)+ D1(1~25fps)	720P(1~30fps)+ D1(1~30fps)
Bit Rate	128K~8192Kbps	
Snapshot	Fastest 1fps JPEG capture	
Video Format	PAL	NTSC
Network		
Ethernet	RJ-45 (10/100Base-T)	
Network Functions	HTTP, TCP/IP, IPv4/IPv6, ARP, IGMP, ICMP, RTSP, RTP, UDP, SMTP, FTP, DHCP, DNS, DDNS, PPPoE, UPNP, NTP, Bonjour, SNMP, Onvif	
Remote Operation	Monitor, PTZ control, Playback, System setting, File download, Log information, Maintenance & Upgrade	
Environmental		
Max. IR Distance	20m	
Power Supply	DC12V, PoE	
Ingress Protection	IP66, 4000V thunder, surge and wave protection	
Power Consumption	Max.4W	
Operating Environment	-10°C~+50°C, 10%~90%	
Dimension	64.43mm x145.02mm	

DH-IPC-HFW2100

Weight	0.35kg
--------	--------

Dimensions (mm)

