HE-IRB60-24-DW









- **⇒ 1/4" S-DIS, 600TVL**
- \Rightarrow 24 Pcs IR LED, 20 Mtr.
- ⇒ Intelligent IR Compensation
- ⇒ Lens: Board Lens 3.6mm
- ⇒ Mechanical IR Cut
- ⇒ Weatherproof IR Camera
- ⇒ Water resistance:IP66
- ⇒ With 3-Axis Bracket
- ⇒ Dimension:180(W) x70(H) x60(D)mm
- ⇒ Power: 12V DC





HE-IRB60-24-DW



Model	HE-IRB60-24-DW
Pick up Element	1/4" Aptina S-DIS
Effective Picture Elements (H×V)	PAL:720(H)x480(V)
Horizontal Resolution	600 TV Lines
Minimum Illumination	0.1 Lux (F1.2 AGC On)
	0Lux (with IR LED ON)
S/N Ratio	More than 52dB
Scanning System	2:1 interface
Synchronous System	Internal
Auto Electronic Shutter	PAL: 1/25s~1/15,000s
Gama Correction	0.45
IR Distance	20 Meters (with ⊄ 5X24PCS Infrared LED)
Video Output	1Vpp, 75Ω
Day& Night:	IR cut filter with auto switch
Power	DC 12V±10%
Lens	Board Lens 3.6mm
Dimension (mm)	180 (W) x70(H) x60(D)
Weight (g)	880
Storage Temperature	-30~+60°C RH95% MAX
Operating Temperature	-20~+45℃ RH95% MAX

Note: Specifications and Product Design are subject to change without notice.