

Specifications

Model	HE-C5001
Hardware	-
CPU	1.2G Dual Core ARM Cortex A7
NPU	600G (0.6T)
RAM	256M DDR3L
ROM	4G EMMC
Camera	Real Sensor 1/2.9 inch FOV 75° 2MP Pixel High-Defination Color Camera WDR Wide Dynamic Sensor 1/5 inch FOV 75° 2MP Pixel Infrared Live Camera
Fill Light	LED Fill Light and Dual Infrared Fill Light (Automatic Control According to Ambient Light)
Display	4.3 Inch Touch Screen, 272*480
Communication Port	TCP/IP, USB-Type A(Support U Disk), Wifi
Product Size	137.5 mm x 87.5 mm x 26 mm
Power	DC 12V, 1A/2A
Working Temperature	0-45 °C
Working Environment	Under Normal Light, Strong Light, Dark Environment, Backlight
Firmware Specs	
OS	Linux 3.0
Language	English, Spanish, Arabic, Thai, Russian, Portuguese, French, Farsi, Vietnamese, Japanese, Turkish and Customizable
Verify Method	Face Recognition, Fingerprint, ID Card(IC optional), Password or Combination
QR Code Scanner	Support (Scan by Camera)
Face / Card / Password Capacity	5000(50000 optional)
Fingerprint Capacity	10000 (100000 optional)
Logs Capacity	500,000
Face Recognition Speed	<0.2S
Face Recognition Distance	0.5~2.5 meters (adjustable)
Live Face Detection	Reject Photo and Video
Mask Detection	Support Mask Detection and Face Recognition with Wearing Mask
Access Control Interface	
Relay Output	One Set
Alarm Output	One Set
Fire Input	One Set
Door Sensor	Support
Wiegand	One SET WG 2G/34 Input/Output
Exit Button	Support
Door Bell	Support