

WIRELESS ALARM KIT

onetouch
communication & security



Security

IoT

Sensors



Intrusion Detection



Panic Alarm



Voice Command



Wifi



Plug & Play



App Control



Works with all
Smart Devices



Motion Detection





Gas Leak Detector

OT-GLD-68B

- Wired / Wireless
- Applicable gas: Coal, Natural, LPG
- Alarm Relay : NO/NC Contact
- Alarm density : 10% LEL
- Alarm mode: Sound/LED Indicator
- Alarm Flash Visibility: 3m
- Alarm speaker volume: ≥ 70 db at 1m
- Installation: Wall mount / Ceiling Mount
- Dimension 107*107*35mm
- CE, EN50194 Certified
- Integration with any 3rd party intrusion panel



Panic Switch

OT-PS-28F

- Wired
- ABS material
- Key reset
- Alarm output: NC/NO option
- Function: Emergency Push Button
- Output: NC/NO/COM
- Electrical life : More then 200,000 times
- Dimension: 86*86*26 mm
- Installation: Flush Mount
- Integration with any 3rd party intrusion panel



Occupancy Sensor

- OT-OS-702

- Wired
- 230V Occupancy Sensor
- Passive Infrared Reduction
- 360 Deg
- 5 Mtr range
- Max Load : 800W
- Delay 15sec to 350 secs



Magnetic Door Sensor

OT-MC-F

- Wired
- Low power consumption
- Output: NC/NO/COM
- Operating Distance : 15 - 20mm
- Installation : Flush Mount
- Integration with any 3rd party intrusion panel