

# PROFICIENT<sup>®</sup>

## AUDIO

### In Ceiling Angled Home Theatre System Package with Triple Driver 10" ultra compact Active Subwoofer 500 watts (5.1, 5.1.2 & 7.1.2)

#### Protégé C651

**Ceiling LCR Speaker with 6-1/2" Polypropylene Woofer and 1" Pivoting Soft-Dome Tweeter.** With the C651, you can build a complete in-ceiling home theatre system at an astoundingly low cost. With its angled drivers, the C651 delivers realistic left/centre/right imaging even though it's mounted in the ceiling. And its high-quality components and careful engineering from our team of audiophiles give it that classic Proficient sound.

#### Protégé C606

**Ceiling Speaker with 6-1/2" Polypropylene Woofer and -3/4" Fixed Soft-Dome Tweeter.** The C606 is our most affordable 6½-inch ceiling speaker. It's a perfect choice for applications where good sound is desired but cost is a major factor. The C606 offers a great combination of sound quality and ease of installation. High sensitivity makes the C606 easy for any amplifier to drive.

#### FDS-10

**Protégé FDS Triple 8" Subwoofer – Multi voltage.** The legacy of innovation and technology from our Sunfire™ Subwoofers lives on in the new Proficient™ Protégé Subwoofer Series. This new line of Subwoofers focuses on compact power and premium performance; we packed a lot into a small box that can only truly be felt in real life. No sound system is complete without a Subwoofer delivering the booms of an action movie, the rich tones of a jazz solo, and the acoustics of a concert hall. Adding a Proficient Protégé Series Subwoofer to a home theatre or media room will transform any listening experience. Proficient Protégé Subwoofer Series – 10". With High back-EMF woofer design: over-sized magnets generating high motor force, experience unprecedented performance at this price



PROFICIENT  
Protégé  
SERIES



# PROFICIENT<sup>®</sup>

## AUDIO

### Other Specifications C651

- 6½" Polypropylene Woofer
- Impedance: 8 Ohms
- 1" Pivoting Silk Dome Tweeter
- Sensitivity: 91dB 1W/1m
- Woofer and Tweeter Bridge Fixed at a 15 Ohms Angle
- Diameter x Depth: 9¼" x 4-9/16"
- Power Handling: 100 Watts
- Ceiling Cut Out: 8¼"
- Frequency Response: 45Hz – 20kHz
- Replaces C650 Ceiling LCR Speaker
- Includes Thin-Bezel Grille held by Neo Magnets

### Other Specifications C606

- 6-½" Polypropylene Woofers
- Impedance: 8Ω
- ¾" Soft Dome Tweeters
- Sensitivity: 90dB 1W/1m
- Power Handling: 75 Watts
- Diameter x Depth: 9-¼" x 3-5/8"
- Frequency Response: 45Hz – 20kHz
- Ceiling Cut Out: 8-¼"
- Replaces C605 Ceiling Speakers
- Includes Thin-Bezel Grilles held by Neo Magnets

### Protege FDS-10 Triple 10" Subwoofer

ITEM U/M  
FDS10 Each

Featuring triple 10" polypropylene drivers with single active woofer and dual passive radiators. Powered by a Class D amplifier with 250 Watt RMS and 500 Watt Peak. Matte black finished cabinet with built-in 5V USB with integrated mount for supported wireless audio kit.

- Amplifier Type: Class D Amp
- Power Rating Continuous: 250 Watts RMS
- Power Rating Peak: 500 Watts Peak
- Frequency Response: 24Hz - 160Hz
- Inputs: Left & Right Line Level, LFE
- Outputs: Line Level High-Pass
- Voltage: 100v - 240v, 50Hz - 60Hz Selectable
- Phase Switch: 0 - 180°
- Crossover: 50Hz - 160Hz
- Finish: Matte Black Finish
- Dampened Rubber Feet
- Dimensions (H x W x D): 13.9" x 13.87" x 13.15"
- Weight: 30.1 lbs

