

QUICK SENSE SERIES - SMOKE AND MULTI DETECTORS

Product Features:

- Advanced detection and discrimination algorithms.
- Easy installation and maintenance.
- Super sleek low-Profile housing design.
- Durable sensor head, no need for replacement.
- SMD circuit board, Design, Satisfactory Quality and Reliability Guaranteed.
- Integrated heat detector for SD 388-2H models.
- N/C (normal/close)-N/O (normal/open) selectable relay output.
- AR (Auto Reset) function for security systems (optional for 4 wire models)
- Two-year limited warranty.
- Size: 102mm diameter with 43mm height only.



The range includes:

QS-388-2	:	2 wire photoelectric smoke alarm
QS-388-2L	:	2 wire photoelectric smoke alarm with remote LED output
QS-388-2H	:	2 wire photoelectric smoke and heat alarm
QS-388-2HL	:	2 wire photoelectric smoke and heat alarm with remote LED output
QS-388-4-24	:	4 wire photoelectric smoke alarm (24VDC)

Product Specification:

Model No.	2/4 wire	Heat Sensor	Volts DC Max./min.	Stand by Current	Alarm Current	Surge Current	Cycle Time	Start Up Time
QS-388-2	2	-	10.8v / 33v	40 micro Amp	55 Mili Amp	100 micro Amp	1-5 Sec.	30 Sec.
QS-388-2L	2	-	10.8v / 33v	40 micro Amp	55 Mili Amp	100 micro Amp	1-5 Sec.	30 Sec.
QS-388-2H	2	135±5°F	10.8v / 33v	40 micro Amp	55 Mili Amp	100 micro Amp	1-5 Sec.	30 Sec.
QS-388-2HL	2	135±5°F	10.8v / 33v	40 micro Amp	55 Mili Amp	100 micro Amp	1-5 Sec.	30 Sec.
QS-388-4-24	4	-	9v / 48 v	40 micro Amp	55 Mili Amp	100 micro Amp	1-5 Sec.	30 Sec.

Specification :

Smoke Sensitivity	0.98--2.40%/FT Obscuration (UL) ; 0.08--0.14 dB/m (EN)
Ceiling Spacing	50 footrating for heat sensor
Temperature Range	-10°C to 50°C F40
Humidity	0 to 95% RH, no condensation or icing
Dimensions	102mm (dia.) x 43mm (ht) with base
Weight	120g/set with base

For Further information please contact at : sales@agnidevices.com , info@agnidevices.com