



Technical Specification	Description
Product	Motorized Retractable Gate
Dimension Width Height	4 m – 30 m 2 m
Opening Direction	Single Side, both side
Mounting Location	Inside/ Outside
Mounting Surface	Wall/ RCC/ Steel
Gate Design	
Gate Frame Material Options	Stainless Steel Gate Frame/ Aluminium Alloy Frame
Bottom guiding track	Single Track. Double Track recommended for Gate Width greater than 7 meters. Trackless recommended for Gate Width less than 8 meters.
Details for Automation System	
Motor Power	250 W
Supply Voltage	220 V/ 50 Hz
Working Temperature	-25 ° C to + 60 °C
Operating Switch	Push button from inside Push Button from outside(Optional)
Accessories (Optional)	Flashing Light Photocell Remote Control with receiver

ACTABLE GATES



- ✓ Folding gates are suitable to restrict pedestrian entry/exit.
- ✓ Designed to work even under extreme climatic situation.
- ✓ Retractable gates are available in S.S/Aluminium material.
- ✓ Wide range of choice for gate design & patterns.
- ✓ Tracked or trackless gates can be provided as per the customized or site requirement.
- ✓ Drive and control unit can be integrated with various accessories to operate the retractable gates.
- ✓ The unique infrared collision avoidance system ensures safety of passengers and vehicles

